



Stick Tape 120 MM*50M

adhesive tape for use bonding waterproof membrane

Technical Data Sheet

Product Descriptions

Sticky Tape(Size:120MM*50M) is a sandwich structure adhesive tape. It is mainly used in detail areas including end laps, strips, penetrations and various tie-ins.



Sticky Tape(Size:120MM*50M) profile

Products type	Usage
40mm × 60 m roll	End laps
150mm × 60 m roll	Strips
1m × 60 m roll	Large area construction

Technical Data/ Typical Properties

Test Item	Test Standard	Typical values
Flexibility at low temperature, -25°C	GB 12953-2003	No Cracking
Peeling Strength, C50 concrete	JC863-2000	0.8N/mm

Features and benefits

- Waterproof- provides effective protection against ground water.
- Adhesive- effective sealing.
- Wide range of application- effect on plastic, rubber and concrete surface.
- Low temperature resistance- function extremely well under adverse condition.

Application Notes

- Do not use below 4°C.
- Remove dirt, dust, debris and loose particles with a wire brush.
- The protective coating surface of the tape should face toward the concrete to be cast.
- Cast concrete with 30 days of application of the tape.

Special Notes



Stick Tape 120 MM*50M

adhesive tape for use bonding waterproof membrane

Technical Data Sheet

- Substrate must be completely clean. All grease, moisture, oil, dust, substrate coatings and other contaminants should be removed.
- Press tape firmly at all terminations with heavy hand pressure or hand roller to maximize adhesion.

Packaging, Storage and Safety

- Protect the materials from all moisture and direct sunlight. The materials should also be free from acid, alkali, oil and organic solvent.
- Stored at ambient temperatures below 45°C.
- 3040 tapes are subject to a shelf life of one year when stored in undamaged, unopened containers. Read product label and Materials Safety Data Sheet before use.

Note Do not leave the sheets exposed for an extended period.

Warranty The company's liability is limited solely to the quality and condition of the material and does not include application not in accordance with the manufacturer's instructions. The applicator must check the product's and system's suitability for their needs and the proper execution of the work. We recommend contacting the company's technical department before using the product to obtain detailed application instructions. We reserve the right to update or modify the data and recommendations without prior notice. It is the applicator's responsibility to stay updated on changes from time to time.