


STICKY TAPE (SIZE:120MM*50M)

Product Descriptions

Sticky Tape(Size:120MM*50M) is a sandwich structure adhesive tape. It is mainly used in detail areas including end laps, strips, penetrations and various tie-ins.



Sticky Tape(Size:120MM*50M) profile

Products type	Usage
40mm × 60 m roll	End laps
150mm × 60 m roll	Strips
1m × 60 m roll	Large area construction

Technical Data/ Typical Properties

Test Item	Test Standard	Typical values
Flexibility at low temperature, -25°C	GB 12953-2003	No Cracking
Peeling Strength, C50 concrete	JC863-2000	0.8N/mm

Features and benefits

- Waterproof- provides effective protection against ground water.
- Adhesive- effective sealing.
- Wide range of application- effect on plastic, rubber and concrete surface.
- Low temperature resistance- function extremely well under adverse condition.

Application Notes

- Do not use below 4°C.
- Remove dirt, dust, debris and loose particles with a wire brush.
- The protective coating surface of the tape should face toward the concrete to be cast.
- Cast concrete with 30 days of application of the tape.

Special Notes

- Substrate must be completely clean. All grease, moisture, oil, dust, substrate coatings and other contaminants should be removed.
- Press tape firmly at all terminations with heavy hand pressure or hand roller to maximize adhesion.

Packaging, Storage and Safety

- Protect the materials from all moisture and direct sunlight. The materials should also be free from acid, alkali, oil and organic solvent.
- Stored at ambient temperatures below 45°C.
- 3040 tapes are subject to a shelf life of one year when stored in undamaged, unopened containers. Read product label and Materials Safety Data Sheet before use.