

א.צ. טכנולוגיות מתקדמות לבנייה הבונים 13 קרית גת ט. 180–980| פ. 08-9240091 08-9240091 azmarketing.co.il בטוח שתצליח



# SAFETY DATA SHEET

according to Regulation 1907/2006/EC, Article 31

Printing Date : 29/11/18

Revision : 29/11/18

Version number 1

TRADE NAME: SARIPBOND SUPERLIGHT - 260

# 1: IDENTIFICATION OF THE SUBSTANCE\ PREPARATION AND OF THE COMPANY UNDERTAKING:

-1.1 Product identifier Trade name: SARIPBOND SUPERLIGHT - 260

- -1.2 Relevant identified uses of the substance or mixture and uses advised against
- **Sector of Use** For Industrial Use Only -Application of the substance / the mixture: Cement Tile Adhesive

**1.3** Details of the supplier of the safety data sheet· Manufacturer/Supplier:Company:A.Z. MARKETING L.T.D.Address:HaBonim 13 st. Kiryat Gat, IsraelTelephone:972-8-9150190 ; Fax: 972-8-9240091www.azmarketing.co.il

*Further information obtainable from: Product safety department. 1.4 Emergency telephone number:* 972-8-9150190

### 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008



**GHS05** Corrosion

Eye Damage 1 H318 Causes serious eye damage



**GHS07** Irritant





# SAFETY DATA SHEET

according to Regulation 1907/2006/EC, Article 31

Printing Date : 29/11/18

Revision : 29/11/18

Version number 1

### TRADE NAME: SARIPBOND SUPERLIGHT - 260

Skin Irrit. 2 H315 Causes skin irritation. Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

2.2 Label Elements Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation Hazards Pictograms: GHS05, GHS07, GHS08 Signal Word: Danger

*Hazard-determining components of labelling: Cement, portland, chemicals calcium oxide,quartz (SiO2)* 

#### Hazard statements

H315 Causes skin irritation. H318 Causes serious eye damage. H317 May cause an allergic skin reaction. H335 May cause respiratory irritation. H373 May cause damage to the lung through prolonged or repeated exposure

#### Precautionary statements

#### Prevention:

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves / eye protection / face protection.
P302+P352 IF ON SKIN: Wash with plenty of water.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P321 Specific treatment (see on this label).

#### Response:

P314 Get medical advice/attention if you fell unwell.
P362+P364 Take off contaminated clothing and wash it before reuse.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/ international regulations.





# SAFETY DATA SHEET

according to Regulation 1907/2006/EC, Article 31

Printing Date : 29/11/18

Revision : 29/11/18

Version number 1

TRADE NAME: SARIPBOND SUPERLIGHT - 260

### 2.3 Other hazards

### -Results of PBT and vPvB assessment

- · PBT: Not applicable.
- · vPvB: Not applicable

### **3 COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.2 Chemical characterisation: Mixtures

- · Description: Mixture of substances listed below with nonhazardous additions
- Dangerous components:

Ingredients	CAS №	EINECS №	Concentration, wt. %
Cement, portland, chemicals	65997-15-1	266-043-4	35-45
Calcium Oxide	1305-78-8	215-138-9	1-3%
Quartz (SiO2)	14808-60-7	238-878-4	> 40
Limestone	1317-65-3		5-10

### Additional information:

For the wording of the listed hazard phrases refer to section 16. -Portland cement clinker:

Consisting of 4 main clinker phases, namely tri- and dicalcium-silicates (3CaO.SiO2 and 2CaO.SiO2), tricalcium-aluminate (3CaO.Al2O3) and tetracalcium-aluminoferrite (4CaO.Al2O3.Fe2O3).

### 4: FIRST AID MEASURES:

### 4.1 Description of first aid measures

- General Information: Consult a physician. Show this safety data sheet to the doctor in attendance.
- After inhalation: Supply fresh air; consult doctor in case of complaints
- After skin contact: Rinse and then wash skin with water and soap.
- · After eye contact:

First rinse with plenty of water for several minutes (remove contact lenses if easily possible), then refer for medical attention.

- · After swallowing: Do NOT induce vomiting. Refer for medical attention.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.





# SAFETY DATA SHEET

according to Regulation 1907/2006/EC, Article 31

Printing Date : 29/11/18

Revision : 29/11/18

Version number 1

# TRADE NAME: SARIPBOND SUPERLIGHT - 260

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · 5.2 Special hazards arising from the substance or mixture

Clinkers are non-combustible and non-explosive and will not facilitate or sustain the combustion of other materials

### Specific hazards:

Explosive dust concentrations. Try to avoid dust forming.

Hazardous decomposition products may be formed under fire conditions (see section 10).

· 5.3 Advice for firefighters

### · Protective equipment:

Portland cement is not flammable Poses no fire-related hazards

Special protective equipment for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

.No available information for special protective equipment for fire fighters

### 6: ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal protection: particulate filter respirator adapted to the airborne concentration of the substance.

See Section 8

· 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Do not sweep. Use dry cleanup methods such as vacuum clean-up overvaccum extraction, which do not cause airborne dispersion.

· 6.4 Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

### 7.0 HANDLING AND STORAGE

### - 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Provide appropriate exhaust ventilation at places where dust is formed. For precautions see section 2.2.

No special precautions are necessary if used correctly.

Follow the recommendations as given under Section 8.

To clean up dry Portland cement see Subsection 6.3.

· Information about fire - and explosion protection: Portland cement is not flammable

#### Advice on safe handling:

For personal protection see section 8. Avoid contact with skin and eyes. Avoid inhalation of dust. Avoid exposure – obtain special instructions before use.

Advice on protection against fire and explosion:

Normal measures for preventive fire protection.





# SAFETY DATA SHEET

according to Regulation 1907/2006/EC, Article 31

Printing Date : 29/11/18

Revision : 29/11/18

Version number 1

# TRADE NAME: SARIPBOND SUPERLIGHT - 260

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Store in cool place. Keep container tightly closed in a dry and well-ventilated place.

Information about storage in one common storage facility:

Dry. Well closed. Separated from strong acids.

Portland cement should be stored under waterproof, dry (i.e. withinternal condensation minimised) conditions, clean and protected from contamination.

Do not use aluminium containers due to incompatibility of the materials.

#### Requirements for storage areas and containers:

Keep container tightly closed in a dry and well-ventilated place. Store in fabric or polypropylene bags with polyethylene liner; multiwall paper bags with polyethylene liner; big bags with polyethylene liner.

· Further information about storage conditions: Protect from moisture.

#### Advice on common storage:

Keep away from food, drink and animal feeding stuffs. Incompatible with acids and bases. Do not store together with oxidizers.

· 7.3 Specific end use(s) No further relevant information available.

### 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### · Additional information about design of technical facilities:

Use: Industrial manufacture/formulation of hydraulic building and construction materials .No further data; see item 7.

### · 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

65997-15-1 Cement, portland, chemicals





# SAFETY DATA SHEET

according to Regulation 1907/2006/EC, Article 31

Printing Date : 29/11/18

Revision : 29/11/18

Version number 1

# TRADE NAME: SARIPBOND SUPERLIGHT - 260

TLV	(respirable fraction): 1 mg/m3, as TWA; A4 (not classifiable as a human carcinogen).		
MAK	carcinogen category: 3B		
1305-78-8 Calcium oxide			
TLV	2 mg/m3, as TWA.		
MAK	(inhalable fraction): 1 mg/m3; peak limitation category: I(2); pregnancy risk group: C.		
EU-OEL	1 mg/m3 as TWA; 4 mg/m3 as STEL		
14808-60-7 Quartz (SiO2)			
TLV	Long term value 0.1mg/m³; respirable fraction		

Additional information: The lists valid during the making were used as basis.

### 8.2 Exposure controls

Avoid contact with skin, eyes and clothing. Wash hands before beaks and immediately after handling the product

Personal protective equipment:

- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Respiratory protection:

When a person is potentially exposed to dust levels above exposure limits, use appropriate respiratory protection. The type of respiratory protection should

be adapted to the dust level

### Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Wear safety goggles.

Body protection: Protective clothing





# SAFETY DATA SHEET

according to Regulation 1907/2006/EC, Article 31

Printing Date : 29/11/18

Revision : 29/11/18

Version number 1

### TRADE NAME: SARIPBOND SUPERLIGHT - 260

### 9: PHYSICAL AND CHEMICAL PROPERTIES

• 9.1 Information on basic physical and chemical properties General Information Appearance

Form: Colour: Odour: • Odour threshold:	Fine Powder White to beige Odorless Not determined
pH-value:	>12.5 (water solution)
Change in condition Melting point/freezing point: Initial boiling point and boiling range: · Flash point: · Flammability (solid, gas): · Decomposition temperature: · Auto-ignition temperature: · Explosive properties: · Explosion limits:	Undetermined. >1000 ° C Not determined Not determined. Not determined. Product is not selfigniting. Product does not present an explosion hazard.
Lower: Upper: Vapour pressure: Density: Relative density Vapour density Evaporation rate Solubility in / Miscibility with water: Partition coefficient: n-octanol/water: Viscosity:	Not determined. Not determined. Not applicable. 1.2-1.8 Not determined. Not applicable. 0.1%-1% (Low solubility) Not determined.
Dynamic: Kinematic: · 9.2 Other information	Not applicable. Not applicable. No further relevant information available.

# **10 : STABILITY AND REACTIVITY**

10.1 Reactivity

When mixed with water, Portland cement will harden into a stable mass that is not reactive in normal environments.





# SAFETY DATA SHEET

according to Regulation 1907/2006/EC, Article 31

Printing Date : 29/11/18

Revision : 29/11/18

Version number 1

## TRADE NAME: SARIPBOND SUPERLIGHT - 260

· 10.2 Chemical stability

· Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions

Reacts with acids, aluminium metals and ammonium salts.

Reacts slowly with water forming hardened hydrated compounds, releasing heat and producing a strong alkaline solution.

· 10.4 Conditions to avoid

Humid conditions during storage may cause lump formation and loss of product quality.

• 10.5 Incompatible materials: Acids, ammonium salts, aluminium or other non-noble metals.

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.





# SAFETY DATA SHEET

according to Regulation 1907/2006/EC, Article 31

Printing Date : 29/11/18

Revision : 29/11/18

Version number 1

### TRADE NAME: SARIPBOND SUPERLIGHT - 260

### **11: TOXICOLOGICAL INFORMATION**

·11.1 Information on toxicological effects

- · Acute toxicity based on available data, the classification criteria are not met.
- Primary irritant effect:
- Skin corrosion/irritation
- Causes skin irritation.
- $\cdot$  Serious eye damage/irritation
- Causes serious eye damage.
- $\cdot$  Respiratory or skin sensitisation
- May cause an allergic skin reaction.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity based on available data, the classification criteria are not met.
- $\cdot$  Carcinogenicity based on available data, the classification criteria are not met.
- Reproductive toxicity based on available data, the classification criteria are not met.
- · STOT-single exposure
- May cause respiratory irritation.
- STOT-repeated exposure based on available data, the classification criteria are not met.
- · Aspiration hazard based on available data, the classification criteria are not met.

### **12: ECOLOGICAL INFORMATION**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- **12.6 Other adverse effects** No further relevant information available.





# SAFETY DATA SHEET

according to Regulation 1907/2006/EC, Article 31

Printing Date : 29/11/18

Revision : 29/11/18

Version number 1

TRADE NAME: SARIPBOND SUPERLIGHT - 260

### **13:DISPOSAL CONSIDERATIONS**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

### **14 :TRANSPORT INFORMATION**

#### 14.1 UN-Number

Portland cement is not covered by the international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID); no classification is required. No special precautions are needed apart from those mentioned under Section 8.

14.2 UN proper shipping name

Void

 14.3 Transport hazard class(es) Not applicable

· 14.4 Packing group

Not applicable

14.5 Environmental hazards:

- Not applicable
- · 14.6 Special precautions for user

Not applicable

- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code
- Not applicable.

### **15 REGULATORY INFORMATION**

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms GHS05, GHS0, GHS08
- · Signal word Danger, Warning





# SAFETY DATA SHEET

according to Regulation 1907/2006/EC, Article 31

Version number 1

Printing Date : 29/11/18

Revision : 29/11/18

### TRADE NAME: SARIPBOND SUPERLIGHT - 260

· Hazard-determining components of labelling:

Cement, Portland chemicals, calcium oxide,quartz(SiO2)

· Hazard statements

H315: Causes skin irritation.

H318: Causes serious eye damage.

H317: May cause an allergic skin reaction.

H335: May cause respiratory irritation

H373: May cause damage to the lung through prolonged or repeated exposure

### · Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P264 Wash thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves / eye protection / face protection. P302+P352 IF ON SKIN: Wash with plenty of water. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 Immediately call a POISON CENTER/doctor. P314 Get medical advice/attention if you fell unwell. P321 Specific treatment (see on this label). P362+P364 Take off contaminated clothing and wash it before reuse. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. P501 Dispose of contents/container in accordance with local/regional/national/ international regulations.

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.





# SAFETY DATA SHEET

according to Regulation 1907/2006/EC, Article 31

Printing Date : 29/11/18

Revision : 29/11/18

Version number 1

### TRADE NAME: SARIPBOND SUPERLIGHT - 260

### **16: OTHER INFORMATION**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### · Relevant phrases

H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H335 May cause respiratory irritation. H373 May cause damage to the lung through prolonged or repeated exposure

· Department issuing SDS: Product safety department.

· Contact:

Company: A.Z. MARKETING L.T.D. Address: HaBonim 13 st. Kiryat Gat, Israel Telephone: 972-8-9150190; Fax: 972-8-9240091 www.azmarketing.co.il

· Abbreviations and acronyms:

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1B: Skin sensitisation – Category 1B
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3