

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name: UNITE Product code: UNITE.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Construction, ready-to-wet mortar

1.3. Details of the supplier of the safety data sheet

Registered company name: PAREXGROUP S.A.

Address: 19, place de la résistance - CS 50053.92445.lssy les Moulineaux Cedex.France.

Telephone: (33)01.41.17.20.00. Fax: 01.41.17.21.30.

fds.matiere-fr@parex-group.com

www.parexlanko.com

For UK: Emergency telephone number: 01827 711755 (Mon - Fri 08:30 - 16:30).

1.4. Emergency telephone number: +33 (0)1 45 42 59 59.

Association/Organisation: INRS / ORFILA http://www.centres-antipoison.net.

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Skin irritation, Category 2 (Skin Irrit. 2, H315).

Serious eye damage, Category 1 (Eye Dam. 1, H318).

Skin sensitisation, Category 1B (Skin Sens. 1B, H317).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms:





GHS05

GHS07

Signal Word: DANGER

Product identifiers:

EC 266-043-4 PORTLAND CEMENT CLINKER

EC 285-561-1 HYDRAULIC LIME

FLUE DUST, PORTLAND CEMENT EC 270-659-9

Hazard statements:

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage.

Precautionary statements - General:

P102 Keep out of reach of children.

Precautionary statements - Prevention:

P261 Avoid breathing dust.

Wear protective gloves/protective clothing/eye protection/face protection. P280

Precautionary statements - Response :

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get

medical advice/attention.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or a doctor.

Precautionary statements - Disposal:

P501 To eliminate the contents / packaging in a waste collection point.

Beforehand, the product should be inerted by hardening in the water and the packagings should

be completely emptied.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition:

| Identification | (EC) 1272/2008 | Note | % |
|------------------------------|---------------------|------|-----------------|
| NDEX: 2076 | | [1] | 25 <= x % < 50 |
| CAS: 14808-60-7 | | | |
| EC: 238-878-4 | | | |
| REACH: EXEMPTE | | | |
| QUARTZ | | | |
| NDEX: 2335 | | [1] | 25 <= x % < 50 |
| CAS: 1317-65-3 | | | |
| EC: 215-279-6 | | | |
| REACH: EXEMPTE | | | |
| NATURAL CALCIUM CARBONATE | | | |
| NDEX: 2999 | GHS07, GHS05 | [1] | 10 <= x % < 25 |
| CAS: 65997-15-1 | Dgr | | |
| EC: 266-043-4 | Skin Irrit. 2, H315 | | |
| REACH: EXEMPTE | Skin Sens. 1B, H317 | | |
| | Eye Dam. 1, H318 | | |
| PORTLAND CEMENT CLINKER | STOT SE 3, H335 | | |
| INDEX: 2270 | GHS07, GHS05 | | 2.5 <= x % < 10 |
| CAS: 85117-09-5 | Dgr | | |
| EC: 285-561-1 | Skin Irrit. 2, H315 | | |
| REACH: 01-2119475523-36-0004 | Eye Dam. 1, H318 | | |
| | STOT SE 3, H335 | | |
| HYDRAULIC LIME | | | |
| NDEX: 2821 | GHS07, GHS05 | | 0 <= x % < 1 |
| CAS: 68475-76-3 | Dgr | | |
| EC: 270-659-9 | Skin Irrit. 2, H315 | | |
| REACH: 01-2119486767-17-0003 | Skin Sens. 1B, H317 | | |
| | Eye Dam. 1, H318 | | |
| FLUE DUST, PORTLAND CEMENT | STOT SE 3, H335 | | |

(Full text of H-phrases: see section 16)

Information on ingredients:

[1] Substance for which maximum workplace exposure limits are available.

SECTION 4: FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation :

Wash nose and throat with water (only if the victim is conscious). Remove the person outdoors to fresh air. In case of respiration trouble, consult

a doctor.

In the event of splashes or contact with eyes:

Rinse IMMEDIATELY with plenty of water for at least 15 minutes holding the eyelids open. Move the eyes in every direction to make sure that all product traces have been removed. Consult an eye doctor.

Do not rub or scratch your eyes.

In the event of splashes or contact with skin:

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

Wash immediately with cold water and soap.

DO NOT use warm water as this will open the pores of the skin and make the fibers penetrate more.

Remove contaminated clothing.

If skin irritation persists, seek medical attention.

DO NOT rub or scratch affected areas.

In the event of swallowing:

For small quantities, rinse the mouth with water and seek medical advice. For large quantities, do not allow the person to drink, do not cause the person to vomit. Transfer the person to a hospital and show the product label or this material safety data sheet to the medical staff on duty.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

Specific and immediate treatment:

Wash copiously with water.

SECTION 5: FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

No data available.

5.2. Special hazards arising from the substance or mixture

No data available

5.3. Advice for firefighters

No data available.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid contact with eyes and skin and breathing dust. Use the product with suitable working clothes (goggles, working-suit, boots,...) and wear a dust mask in case of dust in air.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Use drums to dispose of waste recovered in accordance with applicable regulations (see heading 13).

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

Avoid spilling of powder in large quantities into sewers and waterways.

6.3. Methods and material for containment and cleaning up

Collect product by machine and transfer to suitable container.

After setting, the product can be disposed of as an usual construction waste.

6.4. Reference to other sections

No data available.

SECTION 7: HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

The product should be handled in well-ventilated areas. Avoid the creation of dust. In case of airborne dust, use a powder mask.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid eye contact with this mixture at all times.

Do not breathe dust.

Prohibited equipment and procedures:

No smoking, eating or drinking in areas where the mixture is used.

Never open the packages under pressure.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep out of reach of children.

In dry conditions.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits:

- Germany - AGW (BAuA - TRGS 900, 29/01/2018) :

| CAS | VME : | VME : | Excess | Notes | |
|--|---------|-----------|---------|--------------|----------|
| 65997-15-1 | - | 5 mg/m3 E | - | DFG | |
| - Belgium (Arrêté du 09/03/2014, 2014) : | | | | | |
| CAC | T\A/A . | CTEL . | Cailing | Definition : | Cuitania |

| CAS | IWA: | SIEL: | Ceiling : | Definition : | Criteria : | |
|------------|-----------|-------|-----------|--------------|------------|--|
| 14808-60-7 | 0,1 mg/m³ | | | | | |
| 1317-65-3 | 10 mg/m³ | | | | | |
| 65997-15-1 | 10 mg/m³ | | | | | |

- France (INRS - ED984:2016):

| CAS | VME-ppm: | VME-mg/m3: | VLE-ppm: | VLE-mg/m3: | Notes: | TMP No: | |
|------------|----------|------------|----------|------------|--------|---------|--|
| 14808-60-7 | - | 0.1 A | - | - | - | 25 | |
| 1317-65-3 | - | 10 | - | - | - | - | |

- UK / WEL (Workplace exposure limits, EH40/2005, 2011):

| · · · · · · · · · · · · · · · · · · · | · · · · · · · · · · · · · · · · · · · | · · · · · · · · · · · · · · · · · · · | / | | |
|---------------------------------------|---------------------------------------|---------------------------------------|-----------|--------------|------------|
| CAS | TWA: | STEL: | Ceiling : | Definition : | Criteria : |
| 14808-60-7 | 0.3 mg/m3 | - | - | - | R |
| 1317-65-3 | - ppm | - ppm | | | |
| | 4 mg/m³ | - mg/m³ | | | |
| 65997-15-1 | - ppm | - ppm | | | |
| | 4 mg/m³ | - mg/m³ | | | |

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

PORTLAND CEMENT CLINKER (CAS: 65997-15-1)

Final use: Workers.

Inhalation. Exposure method:

Short term local effects. Potential health effects: DNFI: 3 mg of substance/m3

8.2. Exposure controls

Appropriate engineering controls

Do not rub the eyes with dirty hands.

Anyone with a history of skin sensitisation must on no account handle such products.

Wash hands with cold water and soap before breaks and after handling the product.

Avoid contact with skin, eyes and clothing.

Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE):









Use personal protective equipment that is clean and has been properly maintained.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

Avoid the infiltration of dust into boots and gloves using wristbands and ankle clamps.

Remove and wash gloves, INCLUDING INSIDE, before reuse.

- Eye / face protection

Avoid contact with eyes.

Before handling powders or dust emission, wear mask goggles in accordance with standard EN166.

Prescription glasses are not considered as protection.

Envisage in the vicinity a clean water container or an ocular fountain in the event of projection in the eyes

In case of powder or paste splashing risk, use protective glasses goggles.

- Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Waterproof work gloves or creams.

- Body protection

Avoid skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

Closed working clothes protecting forearms in continuous with gloves. In case of kneeling work, waterproof kneepads are recommended. Ensure that no product remains between the skin and the clothes, the watch, the shoes.

- Respiratory protection

Avoid breathing dust.

Type of FFP mask:

Wear a disposable half-mask dust filter in accordance with standard EN149.

Category:

- FFP2

Powder mask in case of airborne dust.

- Thermal risks

The substance shows no thermal hazard.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information:

| Physical state : | Powder or dust. |
|--|-----------------|
| Important health, safety and environmental information | |
| pH: | Not stated. |
| | Strongly basic. |
| Boiling point/boiling range : | Not relevant. |
| Flash point interval : | Not relevant. |
| Vapour pressure (50°C): | Not relevant. |
| Density: | > 1 |
| Water solubility: | Dilutable. |
| Melting point/melting range : | Not relevant. |
| Self-ignition temperature : | Not relevant. |
| Decomposition point/decomposition range : | Not relevant. |

9.2. Other information

No data available.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Avoid .

- humidity

The mortar can harden in humid conditions.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

No data available.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

May cause irreversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

May have irreversible effects on the eyes, such as tissue damage in the eye, or serious physical decay of sight, which is not fully reversible by the end of observation at 21 days.

Serious eye damage is typified by the destruction of cornea, persistent corneal opacity and iritis.

May cause an allergic reaction by skin contact.

11.1.1. Substances

Acute toxicity:

PORTLAND CEMENT CLINKER (CAS: 65997-15-1)

Dermal route: LD50 > 2000 mg/kg

Species: Rabbit

HYDRAULIC LIME (CAS: 85117-09-5)

LD50 > 2000 mg/kg Oral route:

Species: Rat

OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)

NATURAL CALCIUM CARBONATE (CAS: 1317-65-3)

Oral route: LD50 > 5000 mg/kg

Species: Rat

QUARTZ (CAS: 14808-60-7)

Oral route: LD50 > 2000 mg/kg

Dermal route: LD50 > 2000 mg/kg

Serious damage to eyes/eye irritation:

PORTLAND CEMENT CLINKER (CAS: 65997-15-1)

Corneal haze: Average score = 128

Germ cell mutagenicity:

HYDRAULIC LIME (CAS: 85117-09-5)

Mutagenesis (in vitro): Negative.

Species: Mammalian Cell Line

OECD Guideline 471 (Bacterial Reverse Mutation Assay)

11.1.2. Mixture

Skin corrosion/skin irritation:

In case of damp skin, the partial hydration of cement increases the pH and can irritate the skin. A prolonged contact with a cement paste can induce skin burning.

Serious damage to eyes/eye irritation :

The cement can induce eyelids irritation (blepharitis), corneal irritation (conjunctivitis) and create eyeball injury.

Respiratory or skin sensitisation:

The cement can induce irritation of the respiratory tract and a nasal mucous inflammation. In extreme case, mucous erosion has been observed. Prolonged exposure without proper protection (gloves) can cause skin irritation (fissural dermatitis). In subjects prone to allergies, these lesions may precede an allergy to certain elements present in trace amounts in the cement. Other lesions may be encountered with unprotected prolonged conctact. They usually appear on fingers fissural dermatitis, ulcers, kyperkératoses. May cause an allergic skin reaction.

Other information

If significant swallowed, cement is caustic for the digestive tract, it may cause burns of the mouth, oesophagus and stomach.

SECTION 12 : ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.1. Substances

HYDRAULIC LIME (CAS: 85117-09-5)

Fish toxicity: LC50 = 50.6 mg/l

Duration of exposure: 96 h

Crustacean toxicity: EC50 = 49.1 mg/l

Duration of exposure: 48 h

NOEC = 32 mg/l

Duration of exposure: 14 days

Algae toxicity: ECr50 = 184.57 mg/l

Duration of exposure: 72 h

NOEC = 48 mg/l

Duration of exposure: 72 h

NATURAL CALCIUM CARBONATE (CAS: 1317-65-3)

Fish toxicity: LC50 > 10000 mg/l

Species : Oncorhynchus mykiss Duration of exposure : 96 h

Crustacean toxicity: EC50 > 1000 mg/l

Species : Daphnia magna Duration of exposure : 48 h

Algae toxicity: ECr50 > 200 mg/l

Species: Desmodesmus subspicatus

Duration of exposure: 72 h

12.1.2. Mixtures

The product must not be allowed to run into drains or waterways.

12.2. Persistence and degradability

12.2.1. Substances

HYDRAULIC LIME (CAS: 85117-09-5)

Biodegradability: no degradability data is available, the substance is considered as not

degrading quickly.

12.3. Bioaccumulative potential

none.

12.4. Mobility in soil

none.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

In case of accidental pouring in waste water, the product causes a low pH rise . Cement is a stable material that permanently fixes its compounds and makes them insoluble.

SECTION 13: DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

After curing, the mortar can be removed like other construction debris and stored in landfills in accordance with appropriate regulations.

Waste:

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging:

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste):

17 01 01 concrete

SECTION 14: TRANSPORT INFORMATION

Exempt from transport classification and labelling.

14.1. UN number

-

14.2. UN proper shipping name

_

14.3. Transport hazard class(es)

-

14.4. Packing group

-

14.5. Environmental hazards

14.6. Special precautions for user

-

SECTION 15: REGULATORY INFORMATION

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2017/776 (ATP 10)
- Container information:


No data available.

- Particular provisions :

No data available.

- Standardised American system for the identification of hazards presented by the product in view of emergency procedures (NFPA 704) :

NFPA 704, Labelling: Health=3 Inflammability=1 Instability/Reactivity=1 Specific Risk=none



15.2. Chemical safety assessment

No data available.

SECTION 16: OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3:

| - | |
|------|--------------------------------------|
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) UNITE - UNITE Version 3.1 (03-07-2018) - Page 9/9

| H318 | Causes serious eye damage. |
|------|-----------------------------------|
| H335 | May cause respiratory irritation. |

Abbreviations:

DNEL: Derived No-Effect Level

ADR: European agreement concerning the international carriage of dangerous goods by Road.

IMDG: International Maritime Dangerous Goods. IATA: International Air Transport Association. ICAO: International Civil Aviation Organisation

RID: Regulations concerning the International carriage of Dangerous goods by rail.

GHS05: Corrosion

GHS07 : Exclamation mark

PBT: Persistent, bioaccumulable and toxic. vPvB: Very persistent, very bioaccumulable. SVHC: Substances of very high concern.