

DESOI PowerInject SP20

No. 13576

Description

Spiral pump DESOI PowerInject SP20 is of multiple use and features high power combined with compact design. With the delivery rate control the pump can be controlled continuously from standstill to maximum speed. Optionally, by using an extension cord the delivery rate control can be fixed directly at the end of the material hose so that the operator can react immediately to avoid that the material gets under pressure. Additionally the DESOI PowerInject SP20 can be equipped with the attached mixing device.

Material to be used

- Injection mortar
- Cement paste
- Cement suspension
- Aqueous solution
- DESOI Spiral Anchor Mortar
- Sealing slurries
- Fine filler
- Lime cement plaster

Delivery range

moving device, 30 litre polymer material container, splash guard, rotor, stator, infinitely variable delivery control, Geka coupling, incl. instruction manual

Advantages

- Big material passages - high flow rate
- Cone-shaped material container - self-emptying



1. Infinitely variable delivery rate regulation

Technical data

Supply	230V/50 Hz
Motor power	1.8 kW
Working pressure	max. 15 bar
Delivery - infinitely variable	0 - 13.5 l/min
Grain size (material)	max. 3 mm
Filling height	90 cm
Weight	25 kg
L x W x H	80 x 52 x 90 cm

Accessories

	No.
Spare and wear part set DESOI PowerInject SP20	13577-EVS
Set of tools DESOI PowerInject SP20/110V	13577-WS
Rotor	500-00-285
Stator	500-00-288